# **Manipulators, Probes, Probe Card Holders**



110 / 210 style manipulators



450 / 550 style manipulators



525 / 2525 style manipulators



WAVE style manipulators



Celadon "Versa Tile" mini probe card Micromanipulator offers a variety of manipulators, probe card holders and probes (see reverse). Our manipulators, from the economical model 110 manipulator to the multiversatile WAVE manipulator, all feature direct leadscrewleadnut drives, ergonomic design and the highest stability.

#### Model 110/210: Mini-arc style

- Resolution 32 Threads per inch (TPI) = 2.2 μm
- 10 mm (0.4") max travel each axis

#### Model 450/550 and 2450/2550: Mini-arc style

- Resolution 100 TPI =0.7 μm (450/550) 200 TPI =0.35 μm (2450/2550)
- 6.4 mm (0.25") max travel each axis

#### Model 525 and 2525: Recti-linear style

- Resolution 100 TPI =0.7 μm (525) 200 TPI =0.35 μm (2525)
- 12.7mm (0.5") max travel each axis

## Wave manipulators

"Wave" series manipulators feature X-Y and Z leadscrew-leadnut control plus theta and planarity controls (1) for alignment of microwave, multi-probe or mini-probe cards (such as Celadon's "Versa Tile"

- Resolution 40 TPI =1.7 μm
- 12.7mm (0.5") max travel each axis
- Theta and Planarity range 4 degrees
- Height of PLF / PLS Link arm adjustable up to 3" (75 mm)

(1) Theta and Planarity provided through PLF and PLS Link arms - purchased separately



1555 Forrest Way Carson City, NV 89706

ΓF	: 800.654.5659
РΗ	: 775.882.2400
=X	· 775 882 7694

www.micromanipulator.com · info@micromanipulator.com



9000 series Probe Card Holder



8800 series Probe Card Holder



79 series probe holders



# **Probe Card Holders:**

#### 9000 series Probe Card Holder

- Top load style
- Probe card planarity and theta controls
- · Available in version to support P300 series "top hats"
- For 4.5 " wide cards

## 8800 series Probe Card Holders

- Front or Back load style (reversible)
- Probe card planarity and theta controls
- Available for 4.5 and 6" wide rectangluar cards and 8" round mother / daughter boards

# **Probe Holders**

79 series probe holders

- Available in Triaxial single wire, Triaxial Kelvin (dual wire single tip) or Coaxial configurations
- Available in standard or high temperature versions
- femto ampere resolution, leakage and noise (triaxial)
- Accept disposable series 7 probe tips

# 44 series probes

The 44 series DC-3GHz coaxial probes feature an integrated probe tip (2 micron radius, not disposable) and are available in many configurations:

- · Single tip / single wire or full dual tip / dual wire Kelvin
- Single tip plus ground tip (50 mil (0.050") separation standard, 10 minimum 100 maximum)
- UMC or SMA connectors
- Cables available UMC-UMC, UMC-BNC, UMC-SMA, SMA-SMA
- Capacitance 2.5 pf per inch (probe = 3-6 pf typical)
- Available with series or terminating resistors

## Many other probe holders are available including

- Model 75 single wire general purpose probe holder
- Model 72 single wire malleable shaft probe holders

#### See our full probe and probe holder catalog for more detail